



UNIHEL MIX



UNIHEL MIX is a set of colorants based on organic solvents for industrial coatings. It is based on a universal binder which is compatible with high quality bases for metal and wood coatings. The selected pigments ensure weather and UV stability and mechanical properties of the finished coatings.

Depending on customer's wishes and legislation on a specific market, we create an appropriate TINTING package: we create a set of colorants and MIX bases and according to their characteristics we advise appropriate automatic dispenser with the corresponding software and collection of formulations of shades. **UNIHEL MIX** allows the desired flexibility and independency of mixing different products in very short time.



For additional information about our mixing systems, please send an e-mail to tinting.support@helios.si.

UNIHEL COLORANTS

SOLVENT-
BASED

COLORANTS BASED ON ORGANIC SOLVENTS

UNIHEL colorants are used for shading industrial products (metal) based on organic solvents.

NAME	COLOUR	PIGMENTATION (%)	C.I.	A-SET	P-SET	LIGHT RESISTANCE*	WEATHER RESISTANCE**	DENSITY
UNIHEL paste 01 - white	white	69	PW6	•	•	8	5	2,16
UNIHEL paste 02 - ochre	ochre	54	PY 42	•	•	8	5	1,74
UNIHEL paste 03 - oxide red	oxide red	64	PR 101	•	•	8	5	2,10
UNIHEL paste 04 - green	green	22	PG 7	•	•	8	5	1,26
UNIHEL paste 05 - black	black	26	PBk 7	•	•	8	5	1,18
UNIHEL paste 06 - blue	blue	19	PB 15:4	•	•	8	5	1,11
UNIHEL paste 07 - black NK	black	4,4	PBk 7	•	•	8	5	1,45
UNIHEL paste 08 - red	red	36,7	PR 254	•		8	4-5	1,18
UNIHEL paste 09 - red P	red	10,5	PR 254	•		8	5	1,45
UNIHEL paste 10 - yellow	yellow	43	PY138/PY 184	•		8	5	1,47
UNIHEL paste 11 - orange yellow	orange yellow	29	PY 139	•	•	8	5	1,18
UNIHEL paste 12 - orange	orange	32	PO 36	•		8	4-5	1,18
UNIHEL paste 13 - light ochre	light ochre	64	PBr 24	•	•	8	5	2,01
UNIHEL paste 14 - bordeaux	bordeaux	15	PV 19	•	•	7	4-5	1,07
UNIHEL paste 15 - violet	violet	11	PV 23	•	•	8	5	1,05
UNIHEL paste 16 - magenta	magenta	14	PR 122	•	•	7	4	1,05
UNIHEL paste 17 - yellow Pb	yellow	66	PY 34		•	8	5	2,26
UNIHEL paste 18 - red Pb	red	67,5	PR 104		•	8	5	2,35

* light resistance is measured on an 8-level blue scale; 1 means poor light resistance; 8 means excellent light resistance

** weather resistance is measured on a 5-level grey scale; 1 means poor weather resistance; 5 means excellent weather resistance



Helios TBLUS, d.o.o.
Količevo 65, 1230 Domžale, Slovenia
T +386 1 722 40 00, www.helios-group.eu
Part of KANSAI PAINT.

More information and general terms available at www.helios-group.eu.